

BATTERY CUTTERS

Industrial application



 **holmatro**
mastering power

CIS (Holmatro) Ltd, 25 Hatton Close, Moulton Park Ind. Est., Northampton, NN3 6SU. Tel:- +44(0) 1604 642020 | Fax:- +44(0) 1604 642323

Web:- www.holmatro.co.uk Mail:- sales@holmatro.co.uk



CIS LTD.

HYDRAULIC SOLUTIONS

Battery driven hydraulic cutters for heavy industrial cutting applications. A solution that wasn't available on the market until now. Based on our powerful industrial mobile cutters and the proven technology for our rescue battery cutters, we developed a complete new range of battery cutters specially designed for recycling, demolition, dismantling and replacement industries.

Mastering power

Holmatro's hydraulic equipment and systems are used for different industrial applications around the world. Still, for over 50 years after the foundation in 1967, we keep honoring our traditional Dutch roots and represent innovation, quality and support. That is why we design, develop, manufacture, and test our tools in-house. Our experience with high-pressure hydraulics enables us to seek out the boundaries of what is technically possible. This has made our tools lighter, compacter, more durable, and easier to use. Experience it yourself. Feel the power.

www.holmatro.com

A low-angle photograph of a male worker in a blue uniform, safety glasses, and a grey and orange cap. He is looking upwards and reaching towards the undercarriage of a vehicle that is elevated on a blue hydraulic lift. The background shows the industrial setting of a garage or workshop with concrete walls and blue structural beams.

**NEW!
INDUSTRIAL
BATTERY CUTTERS**

ULTIMATE FREEDOM

Designed around you

Holmatro's industrial battery cutter range is an extension of the current mobile ICU cutter range, only cordless. Cordless simply means that the cord, or in this case 'the hose', has been eliminated, freeing the tool from any external power source. The benefits of cordless, battery-powered tools are obvious. The absence of the hose allows the user a total freedom of movement. The user can start working immediately just by pressing the on-off button. The inline control handle with 360° access is always within reach. And in combination with the ergonomic carrying handle an optimal work comfort is provided, even in the most difficult positions. The battery is positioned on top of the tool. This makes it always accessible and easy to change, even in narrow spaces.

QUICK START





EASY RELOAD



IN ALL POSITIONS (360°)

Quick start

On-off button

Start working immediately just by pressing the on-off button.

In all positions

Inline control handle with 360° access

Centrally placed at the back of the tool, our control handle is always within reach, even in the most difficult positions.

Easy reload

Smart battery position

The battery on top of the tool is always accessible and easy to change, even in narrow spaces.

**WATCH THE VIDEO ON
HOLMATRO.COM/EN/BCU**

UNMATCHED PERFORMANCE

Powerful and fast


Battery tools are emission-free, which makes them healthier for the user and the environment. The battery of Holmatro's new range of cutters is based on the proven lithium-ion battery technology that combines a long battery life with a high capacity for maximum operational use. Therefore, the cutters offer the exact same performance as their hose equivalent, with a maximum cutting force of 65 tonnes. The drive unit of the battery pump contains an ultra-efficient, light and low-noise direct-drive system. A powerful motor drives the hydraulic pump directly, at increased speed. Electronic Speed Control maintains this maximized speed during the entire operation, even at high tool loads or when the battery voltage drops.



POWERFUL & ENERGY EFFICIENT

BRUSHLESS MOTOR


Powerful and extremely energy efficient motor, specially built for the application. Designed for use in hot, cold and wet weather conditions.



NO ENERGY LOSS

DIRECT-DRIVE PUMP

The motor drives the pump directly, without a gear transmission in between. This eliminates mechanical energy loss and provides more usable torque to pump hydraulic fluid.



CONSTANT HIGH SPEED

ELECTRONIC SPEED CONTROL (ESC)

ESC keeps the rpm of the brushless motor (and thus of the hydraulic pump) at a constant maximum level, even at high tool loads or when the battery voltage drops. This results in a continuous, optimally high tool speed.



**WATCH THE VIDEO ON
[HOLMATRO.COM/EN/BCU](https://www.holmatro.com/en/bcu)**

SUSTAINABLE CONSTRUCTION

Ready for tough operating conditions

Holmatro's industrial battery cutters are designed for rugged use in the hardest conditions. The cutters are constructed from high-grade aluminum resulting in strong yet very light tools. They have a very sustainable construction and are outstanding in the safety of their operation. Attributes such as the dead man's function, shielding of all moving parts, greatly limit the chances of accidents happening. The robust housing of the battery pump is all weather proof. That also applies to the electronics inside the battery pump. The circuit board is small and fully sealed to protect it against moisture and dust. The battery tools passed the NFPA required drop testing and have an IP54 protection rating against dust and splashing water from any direction.



SAFE TO OPERATE

MULTIPLE SAFETY FEATURES

Attributes such as the dead man's function, shielding of all moving parts, greatly limit the chances of accidents happening.

DUST & MOISTURE PROOF

SEALED CIRCUIT BOARD

The electronics inside the tool are cast in resin and therefore fully protected against moisture and dust.



ROBUST & LIGHTWEIGHT

HIGH-GRADE ALUMINUM

The cutters are constructed from high-grade aluminum resulting in strong yet very light tools.



**WATCH THE VIDEO ON
HOLMATRO.COM/EN/BCU**

DISCOVER ALL INDUSTRIAL BATTERY CUTTERS

Adequate solutions for almost any cutting application

Holmatro's industrial battery cutters are specially designed for heavy industrial cutting applications, like recycling, demolition, dismantling and replacement. We offer different models and various blade types are available.



BCU 05 A 10



BCU 05 A 30



BCU 05 A 60



BCU 05 A 70

specifications		BCU 05 A 10	BCU 05 A 30	BCU 05 A 60	BCU 05 A 70
art no		100.012.126	100.012.127	100.012.128	100.012.129
blade type		10 cable	30 standard	60 combi	70 GP
cutter typ		mobile	mobile	mobile	mobile
battery included		no	no	no	no
max. working pressure	bar/Mpa	500 / 45	500 / 45	500 / 45	500 / 45
max. spreading opening	mm			266	
max. cutting opening	mm	95	98	191	142
max. spreading force	kN/t			153 / 15.6	
max. cutting force	kN/t	104 / 10.6	124 / 12.6	172 / 17.5	176 / 17.9
protection rate		IP54	IP54	IP54	IP54
required oil content (effective)	cc	37	37	37	37
weight, ready for use	kg	14.7	13.8	13.8	13.9
temperature range	°C	-20 + 55	-20 + 55	-20 + 55	-20 + 55



BCU 10 A 10



BCU 10 A 20



BCU 10 A 30



BCU 10 A 40



BCU 10 A 70

specifications		BCU 10 A 10	BCU 10 A 20	BCU 10 A 30	BCU 10 A 40	BCU 10 A 70
art no		100.012.130	100.012.131	100.012.132	100.012.133	100.012.135
blade typ		10 cable	20 short	30 standard	40 straight	70 GP
cutter typ		mobile	mobile	mobile	mobile	mobile
battery included		no	no	no	no	no
max. working pressure	bar/Mpa	500 / 45	500 / 45	500 / 45	500 / 45	500 / 45
max. spreading opening	mm				305	312
max. cutting opening	mm	115	140	158	296	236
max. spreading force	kN/t				92 / 9.4	92 / 9.4
max. cutting force	kN/t	242 / 24.7	234 / 23.9	246 / 25.1	264 / 26.9	264 / 26.9
protection rate		IP54	IP54	IP54	IP54	IP54
required oli content (effective)	cc	84	84	84	84	84
weight, ready for use	kg	21.5	19.7	19.5	19.6	23.2
temperature range	°C	-20 + 55	-20 + 55	-20 + 55	-20 + 55	-20 + 55

INDUSTRIAL BATTERY CUTTERS




BCU 40 A 20



BCU 40 A 30

specifications		BCU 40 A 20	BCU 40 A 30
art no		100.012.135	100.012.136
blade typ		20 short	30 standard
cutter typ		mobile	mobile
battery included		no	no
max. working pressure	bar/Mpa	500 / 45	500 / 45
max. cutting opening	mm	102	181
max. cutting force	kN/t	594 / 60.6	644 / 65.7
protection rate		IP54	IP54
required oil content (effective)	cc	163	163
weight, ready for use	kg	23.2	23.6
temperature range	°C	-20 + 55	-20 + 55



AVAILABLE ACCESSORIES

Battery cutters

Everything you (may) need for your industrial battery cutter.



Battery BPA



Battery charger



Mains power connector



Battery pouch



Carrying strap

ALL MODELS

required accessories	art no
battery BPA 283 (3.0 Ah)	150.005.823
battery BPA 285 (5.0 Ah)	150.006.208
battery charger BCH1 (220 - 240 VAC)	150.182.208
battery charger BCH2 (100 - 120 VAC)	150.182.209
battery charger BCH3, 12-24 VDC	150.182.286


accessories	art no
mains power connector BMC1 (220 - 240 VAC)	150.182.206
mains power connector BMC2 (100 - 120 VAC)	150.182.207
battery pouch	150.182.214
carrying strap	150.182.249

HOLMATRO OFFICES AND DEALERS

All over the world

Besides the headquarters in the Netherlands, Holmatro has state-of-the-art production facilities and sales offices in the Netherlands and the United States. We have sales offices in China and Poland, and representatives in Germany, Croatia, and India. Together with our global dealer network who are all fully trained at our own training center, we guarantee the same Holmatro standard of quality and a perfect after-sales service for all of our products all over the world.

Find your nearest Holmatro
representative on holmatro.com



Holmatro Netherlands

Raamsdonksveer,
The Netherlands
T +31 (0) 162 58 92 00
E industry@holmatro.com

Holmatro USA

Glen Burnie MD,
USA
T +1 (0) 410-768-9662
E industrial@holmatro-usa.com

Holmatro China

Suzhou, Jiangsu
China
T +86 (512) 6380 7060
E china@holmatro.com

Holmatro Poland

Warszawa,
Poland
T +48 (22) 76 10 404
E info@holmatro.pl

CIS (Holmatro) Ltd, 25 Hatton Close, Moulton Park Ind. Est., Northampton, NN3 6SU. Tel:- +44(0) 1604 642020 | Fax:- +44(0) 1604 642323

Web:- www.holmatro.co.uk Mail:- sales@holmatro.co.uk

Disclaimer - While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. N.V. Holmatro and its affiliated companies (here-after: Holmatro) cannot be held liable in any way for the consequences of activities undertaken based on this printed matter. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (phone number: +31 (0)162-589200). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorization of Holmatro.



CIS LTD.
HYDRAULIC SOLUTIONS

FEEL THE POWER

holmatro.com



Powered by Holmatro



@ByHolmatro



Holmatro Industrial Equipment



Holmatro Industry



Holmatro Industry

CIS LTD.
HYDRAULIC SOLUTIONS

© Holmatro 0418.00 981.000.026

CIS (Holmatro) Ltd, 25 Hatton Close, Moulton Park Ind. Est., Northampton, NN3 6SU. Tel:- +44(0) 1604 642020 | Fax:- +44(0) 1604 642323

Web:- www.holmatro.co.uk Mail:- sales@holmatro.co.uk